

TEROSON VR 700

Known as Silicone Spray June 2015

PRODUCT DESCRIPTION

TEROSON VR 700 provides the following characteristics:

Technology	Lubricant, Release Agent and Restorer for Metals, Rubber and Plastics
Base	Silicone Oil

TEROSON VR 700 is a colourless silicone oil based lubricant and parting agent with a wide variety of uses. It contains only silicone oil and propellant gas and is therefore economical in use. TEROSON VR 700 does not resinify and is resistant to oxidation.

APPLICATION AREAS

TEROSON VR 700 may be used for a variety of purposes. It is used as a lubricant in cars for seat rails, headrests, sliding roofs and aerials. In the home it is used for drawers, curtain rails, door locks, bicycles; and also by tradesmen, e.g. to help draw cables through conduits. It should be noted that the best lubricant is provided for plastic/plastic and plastic/metal combinations. TEROSON VR 700 is not suitable for silicone rubbers. As a release agent TEROSON VR 700 prevents the adhesion of weld spatter to the nozzles of welding equipment and also provides protection against for example door locks and door seal rubbers freezing up. As a restorer TEROSON VR 700 deepens and refreshes the colour of most plastic and rubber components.

TECHNICAL DATA

(Typical Test Results)

Colour	colourless, transparent
Odour	neutral
Consistency	thin liquid
Density	approx. 0.58 g/cm ³
In service temperature range	-30 to 150 °C
short exposure (up to 1h)	200 °C
Aerosol propellant	Propane/butane

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

Shake the can for a short time prior to use and hold the can upright when spraying. TEROSON VR 700 is sprayed onto the part concerned by pressing the spray head, and accurate application can be ensured by inserting the tube. The spray must not be directed onto hot surfaces. Because of the combustible nature of the propellant gas, care should be taken when using TEROSON VR 700 in gas-shielded welding to spray only onto the cold burner tip with the unit switched off. Otherwise there would be a danger that the spray could self-ignite.

STORAGE

Frost sensitive	no
Recommended storage temperature	10 to 20 °C
Shelf life	12 months

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.



TEROSON**TEROSON VR 700**

Known as Silicone Spray June 2015

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany

Phone: +49-211-797-0

www.henkel.com**Henkel Central Eastern Europe GmbH**

A-1030 Wien, Austria

Phone: +43-1711-040

www.henkel.com**Henkel & Cie AG**

CH-4133 Pratteln, Switzerland

Phone: +41-61-825-7000

www.henkel.com